JATMA国内自主規制グレーディング用試験データ提出

ウェットグ リップ性能 ケレーディング

154

転がり抵抗 係数(RRC)

8.5

8.7

LI/SS

75H

75V

申請会社 ブリヂストンタイヤジャパン株式会社

代表サイズ

65 R 14

55 R 15

155

165

偏平率

65's

55's

商品名 ECOPIA EX20C TYPE H

b

提出日 :

2014年6月6日

	単位(N/kN)	_
転がり抵抗係数(RRC)	等級	
RRC≦6.5	AAA	[
6.6≦RRC≦7.7	AA	
7.8≦RRC≦9.0	Α	
9.1≦RRC≦10.5	В	
10.6≦RRC≦12.0	С	

	単位 (%)	
ウェットグリップ性能(G)	等級	
155≦G	а	
140≦G≦154	b	
125≦G≦139	С	
110≦G≦124	d	

L				1	
==+		/ ="	1		
偏平率	<u> </u>	イズ	LI/SS	RRC	ウェット
65's	155	65 R 14	75H	Α	Ь
55's	165	55 R 15	75V	,,	_
					+
			+	1	+
			+	1	+
			+		+

偏平率	サイズ	LI/SS	RRC	ウェット

		偏平率	サイズ	LI/SS	RRC	ウェット
	ŀ					
	ŀ					
	ľ					
	l					
	ļ					
	ŀ					
	ŀ					
	ŀ					
	ŀ					
	ľ					
	l					
	ļ					
	ŀ					
	1					
	ŀ					
	ŀ					
_			!			