

JATMA国内自主規制グレーディング用試験データ提出

申請会社	日本ミシュランタイヤ株式会社	商品名	CROSSCLIMATE 2
------	----------------	-----	----------------

提出日：2024年1月24日
2024年7月30日

偏平率	代表サイズ	LI/SS	転がり抵抗係数(RRC)	グレーディング	ウェットグリップ性能	グレーディング
65's	175 65 R 15	88H XL	8.2	A	146	b
60's	185 60 R 15	84H	8.2	A		
55's	185 55 R 16	83V	8.8	A		
50's	205 50 R 16	87Y	8.2	A		
	185 50 R 16	81H	9.2	B		
45's	205 45 R 16	83H	8.8	A		
40's	205 40 R 17	84W XL	8.6	A		
35's	235 35 R 19	91Y XL	8.3	A		

単位 (N/kN)		単位 (%)	
転がり抵抗係数 (RRC)	等級	ウェットグリップ性能 (G)	等級
RRC ≤ 6.5	AAA	155 ≤ G	a
6.6 ≤ RRC ≤ 7.7	AA	140 ≤ G ≤ 154	b
7.8 ≤ RRC ≤ 9.0	A	125 ≤ G ≤ 139	c
9.1 ≤ RRC ≤ 10.5	B	110 ≤ G ≤ 124	d
10.6 ≤ RRC ≤ 12.0	C		

偏平率	サイズ	LI/SS	RRC	ウェット	偏平率	サイズ	LI/SS	RRC	ウェット	偏平率	サイズ	LI/SS	RRC	ウェット	偏平率	サイズ	LI/SS	RRC	ウェット	偏平率	サイズ	LI/SS	RRC	ウェット			
65's	255 65 R 17	110H	A	b	55's	235 55 R 18	104V XL	A	b	50's	235 50 R 18	101Y XL	A	b	45's	225 45 R 17	94Y XL	A	b	35's	255 35 R 20	97Y XL	A	b			
	215 65 R 16	103V XL				235 55 R 17	103Y XL				225 50 R 19	100V XL				225 45 R 17	91W				255 35 R 19	96Y XL					
	215 65 R 16	102V XL				225 55 R 18	102V XL				225 50 R 17	98Y XL				225 45 R 17	91Y XL				245 35 R 20	95Y XL					
	215 65 R 17	98H				225 55 R 17	101W XL				225 50 R 17	98V XL				215 45 R 17	91Y XL				245 35 R 19	93Y XL					
	195 65 R 15	95V XL				225 55 R 17	101Y XL				235 50 R 18	97V				215 45 R 16	90V XL				235 35 R 19	91Y XL					
	195 65 R 16	92V				235 55 R 18	100V				215 50 R 17	95W XL				205 45 R 17	88W XL				2024年7月30日 追加提出						
	195 65 R 15	92V XL				235 55 R 17	99V				225 50 R 17	94W				205 45 R 17	88V XL				40's	245 40 R 21	100W XL	A	b		
	185 65 R 15	91H				225 55 R 16	99W XL				215 50 R 19	93T				195 45 R 16	84V										
	185 65 R 15	88H				215 55 R 18	99V XL				205 50 R 17	93W XL				205 45 R 17	88V XL										
	175 65 R 15	88H XL				225 55 R 18	98V				205 50 R 17	93V XL				285 40 R 19	107V XL										
	60's	225 60 R 18				104W XL	215 55 R 18				98W XL	225 50 R 16				92Y	255 40 R 20				101V XL						
225 60 R 16		102W XL				225 55 R 17	97Y				215 50 R 17	91W				275 40 R 19	105Y XL										
225 60 R 17		100V XL				215 55 R 16	97V XL				205 50 R 17	89H				255 40 R 19	100Y XL										
215 60 R 17		99V XL				215 55 R 16	97W XL				205 50 R 17	89V				255 40 R 18	99Y XL										
215 60 R 16		99V XL				205 55 R 19	97V XL				195 50 R 16	88V XL				245 40 R 21	100W XL										
215 60 R 16		99H XL				225 55 R 16	95W				205 50 R 16	87Y				245 40 R 19	98Y XL										
215 60 R 17		97W XL				215 55 R 18	95H				185 50 R 16	81H				B	245 40 R 18			97Y XL							
215 60 R 17		96H XL				205 55 R 17	95V XL				255 45 R 19	104V XL				A				235 40 R 19	96Y XL						
205 60 R 16		96V XL				195 55 R 20	95H XL				255 45 R 18	103Y XL								235 40 R 18	95Y XL						
205 60 R 16		96H XL				215 55 R 17	94V				245 45 R 19	102Y XL								245 40 R 18	93Y						
205 60 R 18		96H XL				205 55 R 16	94V XL				245 45 R 18	100Y XL								225 40 R 19	93Y XL						
205 60 R 16		95V XL				215 55 R 16	93V				245 45 R 17	99Y XL								225 40 R 18	92Y XL						
205 60 R 15		95V XL				205 55 R 17	91W				235 45 R 19	99Y XL								215 40 R 18	89V XL						
195 60 R 16		93H XL				205 55 R 16	91H				235 45 R 18	98Y XL								215 40 R 17	87W XL						
195 60 R 16		92H				205 55 R 16	91V				235 45 R 17	97Y XL								205 40 R 18	86W XL						
195 60 R 15		92V XL				195 55 R 16	91V XL				245 45 R 18	96Y								205 40 R 17	84W XL						
195 60 R 15		88H				195 55 R 15	89V XL				245 45 R 17	95Y XL								275 35 R 19	100Y XL						
185 60 R 15	88V XL	195 55 R 16				87H	225 45 R 18				95Y XL	265 35 R 18								97Y XL							
185 60 R 15	88V XL	195 55 R 16				87V	235 45 R 18				94W	255 35 R 18								94Y XL							
185 60 R 15	84H	195 55 R 16				85V	235 45 R 17				94Y XL	245 35 R 18								92Y XL							
		185 55 R 15				83V	225 45 R 17				94Y XL	285 35 R 20								104Y XL							