

# JATMA国内自主規制グレーディング用試験データ提出

申請会社 住友ゴム工業株式会社

商品名 SP SPORT MAXX 060+

提出日 令和3年12月9日

扁平率	サイズ				LI/SS	転がり抵抗係数(RRC)	グレーディング
65's	235	65	R	17	108W XL	8.1	A
55's	205	55	R	16	94W XL	8.9	A
50's	205	50	R	17	93Y XL	9.0	A
45's	245	45	R	18	100Y XL	8.8	A
	205	45	R	17	88Y XL	9.3	B
40's	255	40	R	19	100Y XL	8.7	A
35's	275	30	R	19	100Y XL	8.9	A

ウェットグリップ性能	グレーディング
158	a
158	a

単位 (N/kN)		単位 (%)	
転がり抵抗係数 (RRC)	等級	ウェットグリップ性能 (G)	等級
RRC ≤ 6.5	AAA	155 ≤ G	a
6.6 ≤ RRC ≤ 7.7	AA	140 ≤ G ≤ 154	b
7.8 ≤ RRC ≤ 9.0	A	125 ≤ G ≤ 139	c
9.1 ≤ RRC ≤ 10.5	B	110 ≤ G ≤ 124	d
10.6 ≤ RRC ≤ 12.0	C		

扁平率	サイズ				LI/SS	RRC	ウェット
65's	235	65	R	17	108W	A	a
60's	245	60	R	18	105V	A	
	235	60	R	18	107W	A	
55's	215	55	R	17	94Y	B	
	205	55	R	16	94W	A	
	215	55	R	16	97Y		
	225	55	R	17	101Y		
	235	55	R	20	102V		
	225	55	R	18	102Y		
	235	55	R	17	103Y		
	235	55	R	19	105Y		
	255	55	R	18	109Y		
	255	55	R	19	111W		
50's	205	50	R	17	93Y		
	215	50	R	17	95Y		
	225	50	R	17	98Y		
	245	50	R	18	100Y		
	235	50	R	18	101Y		
	255	50	R	19	107Y		
	275	50	R	20	109W		
	255	50	R	20	109Y		

扁平率	サイズ				LI/SS	RRC	ウェット
45's	205	45	R	17	88Y	B	a
	215	45	R	17	91Y		
	225	45	R	19	92W		
	235	45	R	18	94Y		
	225	45	R	17	94Y		
	225	45	R	18	95Y		
	235	45	R	17	97Y		
	235	45	R	18	98Y		
	245	45	R	17	99Y		
	245	45	R	18	100Y		
	245	45	R	19	102Y		
	245	45	R	20	103Y		
	255	45	R	18	103Y		
	255	45	R	20	105Y		
40's	275	45	R	21	110Y	A	
	275	45	R	20	110Y		
	225	40	R	18	92Y		
	235	40	R	18	95Y		
	235	40	R	19	96Y		
	245	40	R	18	97Y		
	245	40	R	19	98Y		
	255	40	R	19	100Y		
275	40	R	19	105Y			
35's	275	40	R	20	106Y	A	
	295	40	R	21	111Y		

扁平率	サイズ				LI/SS	RRC	ウェット
35's	245	35	R	19	93Y	B	a
	255	35	R	18	94Y	A	
	245	35	R	20	95Y		
	255	35	R	19	96Y		
	265	35	R	18	97Y		
	255	35	R	20	97Y		
	275	35	R	19	100Y		
	275	35	R	20	102Y		
	295	35	R	21	107Y		
	315	35	R	20	110Y		
30's	275	30	R	20	97Y		B