

JATMA国内自主規制グレーディング用試験データ提出

申請会社	横浜ゴム株式会社	商品名	BluEarth-4S AW21
------	----------	-----	------------------

提出日 : 2024年11月1日

偏平率	代表サイズ	LI/SS	転がり抵抗係数(RRC)	グレーディング	ウェットグリップ性能	グレーディング
70's	215 70 R 16	100H	8.9	A	151	b
65's	155 65 R 14	75H	10.4	B	143	b
	215 65 R 16	98H	8.7	A		
60's	165 60 R 15	77H	10.2	B		
	215 60 R 16	99H XL	8.8	A		
55's	165 55 R 15	75V	10.5	B		
	215 55 R 17	98W XL	8.6	A		
50's	195 50 R 19	88H	11.0	C		
	215 50 R 18	92V	10.1	B		
	225 50 R 18	99W XL	9.0	A		
45's	205 45 R 17	88W XL	10.3	B		
40's	245 40 R 18	97Y XL	9.3	B		

単位 (N/kN)		単位 (%)	
転がり抵抗係数 (RRC)	等級	ウェットグリップ性能 (G)	等級
RRC ≤ 6.5	AAA	155 ≤ G	a
6.6 ≤ RRC ≤ 7.7	AA	140 ≤ G ≤ 154	b
7.8 ≤ RRC ≤ 9.0	A	125 ≤ G ≤ 139	c
9.1 ≤ RRC ≤ 10.5	B	110 ≤ G ≤ 124	d
10.6 ≤ RRC ≤ 12.0	C		

偏平率	サイズ	LI/SS	RRC	ウェット
70's	215 70 R 16	100H	A	b
65's	155 65 R 14	75H	B	
	165 65 R 14	79H		
	175 65 R 14	82T		
	175 65 R 15	84H		
	185 65 R 15	88H		
	195 65 R 15	91H		
	205 65 R 16	95H		
	215 65 R 16	98H		
	225 65 R 17	106V/XL		
60's	165 60 R 15	77H	B	
	185 60 R 15	88H/XL		
	195 60 R 17	90H		
	205 60 R 16	96H/XL	A	
	215 60 R 16	99H/XL		
	215 60 R 17	100V/XL		
	225 60 R 17	103V/XL		
	225 60 R 18	104V/XL		
	235 60 R 18	107W/XL		

偏平率	サイズ		LI/SS	RRC	ウェット
55's	165	55 R 15	75V	B	b
	185	55 R 15	86H/XL		
	195	55 R 16	87H		
	205	55 R 16	91V		
	205	55 R 17	95V/XL		
	225	55 R 18	98V		
	215	55 R 17	98W/XL		
	215	55 R 18	99V/XL	A	
	225	55 R 19	99V		
	235	55 R 18	100V		
	225	55 R 17	101W/XL		
235	55 R 20	102W			
50's	235	55 R 19	105W/XL	C	b
	195	50 R 19	88H		
	215	50 R 18	92V	B	
	205	50 R 17	93V/XL		
	215	50 R 17	95W/XL		
	225	50 R 17	98V/XL		
	225	50 R 18	99W/XL	A	

偏平率	サイズ				LI/SS	RRC	ウェット
50's	235	50	R	18	101V/XL	A	b
	235	50	R	20	104W/XL		
45's	205	45	R	17	88W/XL	B	
	215	45	R	17	91W/XL		
	215	45	R	18	93V/XL		
	225	45	R	17	94V/XL		
	225	45	R	18	95Y/XL		
	235	45	R	18	98Y/XL		
40's	245	40	R	18	97Y/XL		