

JATMA国内自主規制グレーディング用試験データ提出

申請会社	横浜ゴム㈱	商品名	BluEarth-Es ES32
------	-------	-----	------------------

提出日 : 令和3年9月3日

扁平率	代表サイズ				LI/SS	転がり抵抗係数(RRC)	グレーディング
80's	135	80	R 12	68S	8.6	A	
70's	145	70	R 12	69S	8.3	A	
65's	145	65	R 13	69S	8.2	A	
	195	65	R 16	92V	7.8	A	
	195	65	R 15	91S	7.4	AA	
	215	65	R 15	96S	7.2	AA	
60's	165	60	R 14	75T	8.8	A	
	195	60	R 15	88H	8.5	A	
	225	60	R 17	99H	7.1	AA	
55's	155	55	R 14	69V	8.5	A	
	195	55	R 15	85V	9.0	A	
	225	55	R 18	98V	6.9	AA	
50's	165	50	R 15	73V	8.8	A	
	195	50	R 15	82V	9.0	A	
	235	50	R 18	97W	7.1	AA	
45's	205	45	R 16	83V	9.0	A	
	225	45	R 18	95W XL	7.4	AA	
40's	205	40	R 17	84V XL	8.7	A	
35's	225	35	R 19	84W	7.8	A	

ウェットグリップ性能	グレーディング
131	c
143	b

単位 (N/kN)		単位 (%)	
転がり抵抗係数 (RRC)	等級	ウェットグリップ性能 (G)	等級
RRC ≤ 6.5	AAA	155 ≤ G	a
6.6 ≤ RRC ≤ 7.7	AA	140 ≤ G ≤ 154	b
7.8 ≤ RRC ≤ 9.0	A	125 ≤ G ≤ 139	c
9.1 ≤ RRC ≤ 10.5	B	110 ≤ G ≤ 124	d
10.6 ≤ RRC ≤ 12.0	C		

扁平率	サイズ				LI/SS	RRC	ウェット
80's	135	80	R 12	68S	A	c	
	145	80	R 12	74S			
	145	80	R 13	75S			
	155	80	R 13	79S			
	165	80	R 13	83S			
	175	80	R 14	88S			
70's	145	70	R 12	69S	A	c	
	155	70	R 12	73S			
	155	70	R 13	75S			
	165	70	R 13	79S			
	165	70	R 14	81S			
	175	70	R 13	82T			
	175	70	R 14	84S			
	185	70	R 13	86S			
	185	70	R 14	88S			
	195	70	R 14	91H			
65's	215	70	R 15	98S	A	c	
	145	65	R 13	69S			
	145	65	R 15	72H			
	155	65	R 13	73S			
	155	65	R 14	75S			
	165	65	R 13	77S			
	165	65	R 14	79S			
	165	65	R 15	81S			
	175	65	R 14	82S			
	175	65	R 15	84S			

扁平率	サイズ				LI/SS	RRC	ウェット
65's	185	65	R 14	86T	A	b	
	185	65	R 15	88S			
	195	65	R 14	89H			
	195	65	R 16	92V			
	205	65	R 15	94H			
	205	65	R 16	95H			
	215	65	R 16	98H			
	195	65	R 15	91S			
	215	65	R 15	96S			
	60's	165	60	R 14			75T
165		60	R 15	77H			
175		60	R 14	79H			
175		60	R 15	81H			
175		60	R 16	82H			
185		60	R 14	82H			
185		60	R 15	84H			
185		60	R 16	86H			
195		60	R 15	88H			
195		60	R 16	89H			
195		60	R 17	90H			
205		60	R 15	91H			
205		60	R 16	92H			
215		60	R 16	95H			
215	60	R 17	96H				
225	60	R 17	99H				

扁平率	サイズ				LI/SS	RRC	ウェット
55's	155	55	R 14	69V	A	c	
	165	55	R 14	72V			
	165	55	R 15	75V			
	175	55	R 15	77V			
	185	55	R 15	82V			
	185	55	R 16	83V			
	195	55	R 15	85V			
	195	55	R 16	87V			
	205	55	R 15	88V			
	205	55	R 16	91V			
50's	215	55	R 16	93H	A	b	
	215	55	R 17	94V			
	225	55	R 17	97W			
	225	55	R 18	98V			
	165	50	R 15	73V			
	165	50	R 16	75V			
	195	50	R 15	82V			
	195	50	R 16	84V			
	205	50	R 16	87V			
	205	50	R 17	89V			
45's	215	50	R 17	95V XL	AA	b	
	225	50	R 16	92V			
	225	50	R 17	94V			
	225	50	R 18	95V			
	235	50	R 17	94V			
	235	50	R 18	97W			

扁平率	サイズ				LI/SS	RRC	ウェット
45's	205	45	R 16	83V	A	b	
	215	45	R 17	91V XL			
	215	45	R 18	93W XL			
	225	45	R 17	94V XL			
	235	45	R 17	97V XL			
	225	45	R 18	95W XL			
40's	205	40	R 17	84V XL	A	b	
	215	40	R 17	87V XL			
	215	40	R 18	85W			
	225	40	R 18	92W XL			
	235	40	R 18	95W XL			
	245	40	R 18	93W			
35's	245	40	R 19	94W	A	b	
	225	35	R 19	84W			
	255	35	R 18	90W			
	265	35	R 18	93W			